

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 June 2004 (03.06.2004)

PCT

(10) International Publication Number
WO 2004/045442 A1

(51) International Patent Classification⁷: **A61B 18/14**

(74) Agents: **MORRIS, James, H.** et al.; Wolf, Greenfield & Sacks, P.C., 600 Atlantic Avenue, Boston, MA 02210 (US).

(21) International Application Number:
PCT/US2003/036488

(81) Designated States (*national*): JP, US.

(22) International Filing Date:
17 November 2003 (17.11.2003)

(84) Designated States (*regional*): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/426,735 15 November 2002 (15.11.2002) US

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(71) Applicant (for all designated States except US):
C.R.BARD, INC. [US/US]; 730 Central Avenue, Murray Hill, NJ 07974 (US).


(72) Inventor; and

(75) Inventor/Applicant (for US only): **KOZEL, Peter, D.** [US/US]; 519 Bedford Street, Concord, MA 01742 (US).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



(54) Title: **ELECTROPHYSIOLOGY CATHETER WITH ABLATION ELECTRODE**



(57) **Abstract:** In one embodiment, a shaft-mounted electrode for ablating tissue comprises an end portion and a middle portion. The end portion is configured differently than the middle portion such that, when the electrode is energized, the ratio of a first density of ablation energy that is emitted in a vicinity of the end portion to a second density

of ablation energy that is emitted in a vicinity of the middle portion is lower than the ratio would be if the end portion were configured the same as the middle portion. In another embodiment, a shaft-mounted electrode for ablating tissue comprises at least two separate coiled conductors having interleaved spirals.

WO 2004/045442 A1

THIS PAGE BLANK (USP 0

ELECTROPHYSIOLOGY CATHETER WITH ABLATION ELECTRODE**Background**

The human heart is a very complex organ, which relies on both muscle contraction and electrical impulses to function properly. The electrical impulses travel through the heart walls, first through the atria and then the ventricles, causing the corresponding muscle tissue in the atria and ventricles to contract. Thus, the atria contract first, followed by the ventricles. This order is essential for proper functioning of the heart.

In some individuals, the electrical impulses of the heart develop an irregular propagation, disrupting the heart's normal pumping action. The abnormal heartbeat rhythm is termed a "cardiac arrhythmia." Arrhythmias may occur when a site other than the sinoatrial node of the heart is initiating rhythms (i.e., a focal arrhythmia), or when electrical signals of the heart circulate repetitively in a closed circuit (i.e., a reentrant arrhythmia).

Techniques have been developed which are used to locate cardiac regions responsible for the cardiac arrhythmia, and also to disable the short-circuit function of these areas. According to these techniques, electrical energy is applied to a portion of the heart tissue to ablate that tissue and produce scars which interrupt the reentrant conduction pathways or terminate the focal initiation. The regions to be ablated are usually first determined by endocardial mapping techniques. Mapping typically involves percutaneously introducing a catheter having one or more electrodes into the patient, passing the catheter through a blood vessel (e.g. the femoral vein or artery) and into an endocardial site (e.g., the atrium or ventricle of the heart), and deliberately inducing an arrhythmia so that a continuous, simultaneous recording can be made with a multichannel recorder at each of several different endocardial positions. When an arrhythmogenic focus or inappropriate circuit is located, as indicated in the electrocardiogram recording, it is marked by various imaging or localization means so that cardiac arrhythmias emanating from that region can be blocked by ablating tissue. An ablation catheter with one or more electrodes can then transmit electrical energy to the tissue adjacent the electrode to create a lesion in the tissue. One or more suitably positioned lesions will typically create a region of necrotic tissue which serves to disable the propagation of the errant impulse caused by the arrhythmogenic focus. Ablation is

carried out by applying energy to the catheter electrodes. The ablation energy can be, for example, RF, DC, ultrasound, microwave, or laser radiation.

It is known that, rather than using a cylindrical or ring-shaped electrode, an electrode may be formed by wrapping a conductor successively around a catheter so that adjacent "windings" of the conductor touch each other. Such a configuration is generally employed to simulate the electrical behavior of a ring shaped electrode but at the same time to make the electrode-covered portion of the catheter flexible, thereby permitting the electrode to form curved lesion patters.

It is also known that certain physical and electrical advantages can be achieved. by introducing spaces between the successive windings of the electrodes. Such advantages are discussed, for example, in U.S. Patent No. 6,030,382 ("the '382 patent"). The electrode configurations described in the '382 patent, however, still suffer from a number of significant drawbacks that limit their performance capabilities. Those disadvantages, and the manner in which various aspects of the invention can be employed to overcome them, are discussed below.

Summary of the Invention

According to one aspect of the present invention, a shaft-mounted electrode for ablating tissue comprises an end portion and a middle portion. The end portion is configured differently than the middle portion such that, when the electrode is energized, the ratio of a first density of ablation energy that is emitted in a vicinity of the end portion to a second density of ablation energy that is emitted in a vicinity of the middle portion is lower than the ratio would be if the end portion were configured the same as the middle portion.

According to another aspect of the invention, a shaft-mounted electrode for ablating tissue comprises at least an end portion and a middle portion, and has at least one energy emitting area configured in a shape other than a coil. At least the middle portion is configured and arranged to introduce edge effects in the middle portion such that, when the conductor is energized, the ratio of a first density of ablation energy emitted in a vicinity of the end portion to a second density of ablation energy emitted in a vicinity of the middle portion is lower than the ratio would be if the electrode were not configured and arranged to introduce such edge effects in the middle portion.

According to another aspect, a shaft-mounted electrode for ablating tissue comprises at least two separate coiled conductors having interleaved spirals.

According to yet another aspect, a shaft-mounted electrode for ablating tissue comprises a coiled conductor having spaces between at least some of its spirals. The
5 electrode is mounted on the shaft such that at least a portion of an end of the electrode is disposed at least partially below an annular surface of the shaft that is adjacent the end of the electrode.

According to yet another aspect, a shaft-mounted electrode for ablating tissue comprises an end portion and a middle portion, and has at least one energy emitting area
10 configured in a shape other than a coil. The electrode further comprises means for introducing edge effects in at least the middle portion.

Brief Description of the Drawings

Fig. 1 is a block diagram illustrating a system in which embodiments of the
15 present invention may be employed; and

Figs. 2-11 each shows a distal end of a catheter having one or more electrodes mounted on it in accordance with a respective embodiment of the invention.

Detailed Description

20 A conventional ring-shaped electrode exhibits a non-uniform electric field when energized. In particular, the electric field will be strongest at the ends of the electrode due to the increased current density caused by so-called "edge effects" (also sometimes referred to as "fringing" or "charge crowding") in those regions. Coiled electrodes that have abutting windings, like those depicted in Figs. 5 and 6 of the '382 patent, behave
25 similarly to conventional electrodes in terms of their exhibited edge effects.

Recognizing the foregoing, two alternative approaches are disclosed herein for ameliorating this undesirable result. The resulting structures are electrodes that can create at least same basic types of lesion patterns as conventional electrodes, but that emit ablation energy of a more uniform density along the electrode's entire length,
30 thereby creating more uniform lesion patterns than their predecessors.

The first such approach disclosed herein involves introducing additional edge effects throughout the electrode to thereby minimize the adverse impact of the edge effects at the ends. That is, edge effects may be created intentionally at least in the

middle portion of the electrode so as to bring the current density in the middle portion of the electrode more in line with the enhanced current density caused by the edge effects at the ends. A number of alternative techniques and structures for achieving this basic objective are disclosed below. Although the '382 patent discloses coiled electrodes
5 having spaces between coil windings (e.g., Figs. 7 and 8) that would appear to inherently achieve the goal of introducing edges throughout a coiled electrode, the teaching of the '382 patent is limited to coil electrodes. It does not disclose or suggest introducing additional edges into any other type of electrode structure.

As the gaps between spirals of a coiled electrode become smaller, more
10 electromagnetic coupling occurs between the spirals and the electrode behaves more like a conventional ring electrode insofar as edge effects at the electrodes' ends are concerned. The benefit of introducing additional edges throughout the electrode therefore diminishes as the spirals are brought closer together. It is thus desirable to keep the gaps relatively large so as to maximize that benefit. If the gaps are made too
15 large, however, the electrode may not ablate tissue evenly, i.e., a scalloped, rather than uniform, ablation pattern may result. Advantageously, in accordance with an aspect of the invention, the spirals of two or more electrically isolated electrodes may be interleaved with each other so that the width of the gaps between each electrode's spirals can be increased, while still creating a uniform lesion pattern by separately energizing each of
20 the respective electrodes.

The second approach disclosed herein for minimizing the adverse impact of edge effects in an ablation electrode involves somehow causing the portions of the electrode that are subjected to higher current densities due to edge effects to be responsible for ablating more tissue than the other portions of the electrode, thereby ensuring that the
25 tissue along the entire path of an intended lesion pattern is subjected to a substantially uniform density of ablation energy. A number of techniques for achieving this objective also are disclosed, including, for example, separating spirals of a coiled electrode at locations near the ends of the electrode, while not separating, or separating to a lesser extent, the spirals in the inner portion of the coiled electrode.

30 It should be appreciated that coiled electrodes having uniform spacing between adjacent windings, like those depicted in Figs. 7 and 8 of the '382 patent (discussed above), also suffer from "edge effects" at their ends. Indeed, as noted above, the significance of the edge effect at the ends of such a coiled electrode tends to increase as

the spacing between the spirals becomes smaller. Notably, in an effort to maximize the flexibility of its electrodes and facilitate the placement of temperature sensing elements, the '382 patent suggests exactly the opposite approach as that suggested herein. That is, for the electrodes depicted in Figs. 12 and 13 of the '382 patent, it is suggested that the electrode windings be spaced closer together at the electrode's ends than in the middle. This suggested spacing of the windings would tend to exacerbate the edge effect problem of the electrode, rather than ameliorate it, because the portions of the electrode having the highest current densities would also be the portions having the largest number of windings per unit length.

Fig. 1 illustrates an overview of a catheter system that may be used in electrophysiology procedures in accordance with embodiments of present invention. The system may include a catheter 1 having a flexible shaft 3 and a control handle 5. An ablation energy generator 7 may be used for generating ablation energy when the catheter 1 is used in ablation applications, and may transmit ablation energy to the catheter 1 via a controller 9 and a cable 11. A recording device 13 may optionally be included in the catheter system to record signals originating from the catheter 1, e.g., from an electrode or temperature sensor on the catheter.

The controller 9 may, for example, be a QUADRAPULSE RF CONTROLLER™ device available from C.R. Bard, Inc., Murray Hill, New Jersey. As shown, the ablation energy generator 7 may be connected to the controller 9 via a cable 15. The recording device 13 may be connected to the controller 9 via a cable 17. When used in an ablation application, the controller 9 may be used to control ablation energy, provided by the ablation energy generator 7, to the catheter 1. When used in a recording application, the controller 9 may be used to process signals from the catheter 1 and provide these signals to the recording device 13. Although illustrated as separate devices, the ablation energy generator 7, recording device 13, and/or controller 9 may be incorporated into a single device. It should further be appreciated that although both the ablation energy generator 7 and recording device 13 are illustrated in Fig. 1, both of these devices need not be incorporated in the catheter system in accordance with the present invention.

Although the embodiment of Fig. 1 and the description that follows shows and describes the electrode 21 as being mounted on a catheter, it should be appreciated that an electrode configured according to one or more aspects of the invention may

alternatively be mounted on any type of shaft or probe, and the invention is not necessarily limited to a catheter-mounted electrode.

As shown, the catheter 1 of Fig. 1 may include a distal end 19 having an electrode 21. As described below, a number of different constructions are possible for the one or more electrodes that may be included on the distal end 19 of the catheter 1, or other electrode-carrying device.

Fig. 2 illustrates the distal end 19 of the catheter 1 (Fig. 1) having an electrode 23 shaped in a coil configuration, similar to the electrodes shown, for example, in Figs. 5 and 6 of the '382 patent (discussed above). Like those electrodes, the coil shape of the electrode 23 permits it to be flexed to at least some degree. The electrode 23 may be, for example, between approximately 4 mm and 10 mm in length so as to provide a sufficient surface area for tissue ablation. Flexibility of the electrode 23 may be useful, for example, when the catheter 1 is a steerable catheter, so that the electrode may be flexed as the corresponding portion of the shaft 3 is maneuvered. Flexibility of electrode 23 may also be useful for conforming the electrode to anatomy and for use with catheters that are shaped to or have the capability of conforming to anatomy.

Unlike the electrodes disclosed in the '382 patent, the conductors of the electrode 23 are recessed within the outer circumferential surface of the distal end 19 so as to provide a low or flush profile. A low or flush profile may increase the safety of the catheter by reducing the risk of damage to the tissue caused by the electrode. While the embodiment of Fig. 2 shows an electrode that is fully recessed, i.e., the outer surface of the electrode 23 is substantially flush with the outer surface of the portions of the catheter body that abut the edges 25, it should be appreciated that the electrode may alternatively be recessed only partially within the catheter body so that the windings of the electrode 23 protrude slightly above the outer surface of the body of the catheter 1.

An electrode constructed in the manner shown in Fig. 2 may possess some potentially undesirable electrical properties. For example, when an RF signal is applied to such an electrode, electric fields are generated that are distributed within the electrode in an uneven manner. Typically, the electric fields will be greatest at the boundaries of the electrode and, particularly, at any boundary having a sharp transition. As noted above, this phenomenon is variously referred to as an edge effect, fringing, or charge crowding. In the electrode 23 of Fig. 2, the greatest edge effect occurs at each end 25 of

the electrode. A similar edge effect may be observed at the ends of a conventional ring-shaped electrode.

Because an electrode exhibiting edge effects yields an uneven distribution of applied RF energy, charring of tissue or coagulation of blood may result if the electrode is used in an ablation electrophysiology catheter procedure. Further, lesions will tend to develop more quickly in tissue in contact with regions of the electrode having a higher concentration of RF energy, which may limit the ability of the electrode to create deep and/or continuous lesions. An additional challenge exists for electrodes having a longer length, as it becomes more difficult to uniformly deliver energy at all points on the surface of an electrode as the surface area of the electrode increases.

Fig. 3 illustrates the distal end 19 of the catheter 1 having an electrode 29 in accordance with another embodiment of the invention. As shown, the electrode 29 of Fig. 3 is similar to the electrodes shown in Figs. 7 and 8 of the '382 patent in that the coiled electrode comprises a conductor forming a series of spirals 31, where adjacent spirals 31 are separated by gaps 33. As with the embodiment shown in Fig. 2, however, the spirals of an electrode may be at least partially recessed within the catheter body so as to form a flush or low profile.

The inclusion of gaps 33 between the spirals 31 result in edge effects being created at the two edges of each spiral 31, along the entire length of the electrode 29, rather than just at the ends 28 of the electrode 29. Thus, the introduction of these additional edges serves to reduce the significance of the edge effects at the ends 28, thereby causing the distribution of current densities (and resulting electric field strength) to be more uniform along the length of the electrode. In practice, the uniformity in the electric field strength between the ends 28 and the middle 30 of the electrode 29 tends to increase as the width of the gaps 33 increases. The reason this occurs is that, as the gaps become smaller, the electromagnetic coupling (or proximity effect) between the spirals causes the electrode 29 to behave more like a traditional ring electrode in terms of its edge effects, i.e., it exhibits more pronounced edge effects at its ends 28.

Thus, as the distance between spirals 31 increases, the flux linkage between the spirals decreases, and a more uniform current density along the length of the electrode 29 is achieved. However, if the distance between the spirals 31 is too large, the density of spirals per unit length may be insufficient to create a beneficial lesion during ablation, or an undesirable scalloped lesion pattern may be formed. Thus, it is desirable to choose an

optimum balance between reduced electromagnetic influence between spirals and efficacy of ablation. This results in more uniform energy delivery and therefore reduces charring and increases the uniformity of lesions. In one example implementation of the electrode 29 of Fig. 3, the gaps 31 are approximately the same width as the spirals 33.

5 Fig. 4 illustrates an electrode configuration that allows an increased distance between spirals, thereby minimizing the edge effect at the ends of the electrode, while at the same time maintaining a suitable density of spirals per unit length. As shown, the distal end 19 of the catheter 1 may include an ablation electrode 54 comprising a first conductor 57 having spirals 56 interleaved between spirals 58 of a second conductor 59. 10 The first and second conductors 57, 59 of the electrode 54 may be electrically isolated from one another and independently energized. For example, each of the first and second conductors 57, 59 may be respectively connected to controller 9 (Fig. 1) via first and second wires (not shown), and may receive different signals. In one example, the first and second conductors 57, 59 are energized individually in a pulsed sequential fashion 15 for complete thermal coverage.

It should be appreciated that a number of variations on the described embodiment are possible. For example, an electrode may be provided having three or more conductors with interleaved spirals, and such conductors may be energized in a sequential or even a random fashion. The spirals of the various conductors may also be 20 spaced from one another either in a uniform or non-uniform pattern (e.g., with spaces between spirals being greater at the ends of the electrode than in the middle), rather than being contiguous as shown in the illustrated embodiment, so as to achieve additional advantages discussed herein. Moreover, the conductors forming the spirals may be completely recessed within the body of the catheter 1 so that the upper surface of the 25 conductor/body junction is substantially flat (as illustrated in Fig. 4), may be partially recessed within the body of the catheter 1 so that only a slight protrusion of spirals results, or may simply be disposed on top of the catheter's body without the catheter body being recessed in any fashion.

Fig. 5 illustrates a further embodiment of the invention in which spirals 49 of an 30 electrode 47 are spaced along the length of the electrode 47 so as to minimize the impact of edge effects near the edges 60. In the example embodiment shown, the spirals 49 of electrode 47 are contiguous in the center portion 53 of the electrode, while gaps 51 exist between the spirals 49 in the end portions 55 of the electrode 47. In one implementation,

these gaps 51 may be approximately equal in width to the width of the wire of the electrode 47. In the configuration of Fig. 5, although the electrode 47 will exhibit an uneven current distribution when energized, the evenness of the distribution of heat within the tissue along the length of electrode 47 will be improved significantly because
5 the spirals are spaced further apart in the end portions 55 (where the current densities are highest due to edge effects in those regions) than in the middle portion 53.

Alternatively, as illustrated in Fig. 6, gaps 62 between spirals 66 of an electrode 61 may be created so that they are largest near the ends 68 of the electrode 61, and gradually become smaller toward the middle 70 of the electrode 61. Ideally, a spacing
10 can be achieved using this technique by which the greater spacing near the ends 68 accounts exactly for the greater current density in those regions due to edge effects, thereby achieving a substantially uniform thermal profile across the entire length of the electrode 61.

As with the other embodiments described above, it should be appreciated that the
15 conductors forming the spirals in the embodiments of Figs. 5 and 6 may be completely recessed within the body of the catheter 1 so that the upper surface of the conductor/body junction is substantially flat (as illustrated in Fig. 5), may be partially recessed within the body of the catheter 1 so that only a slight protrusion of spirals results, or may simply be disposed on top of the catheter's body without the catheter body being recessed in any
20 fashion (as illustrated in Fig. 6). In the latter two cases, the protrusion of the electrode may enhance contact between the electrode and the tissue being ablated.

In addition, it should be appreciated that the foregoing technique of spacing the spirals more closely together in the middle portion of an electrode than near the ends may also be employed with a multiple conductor configuration such as that described
25 above in connection with Fig. 4.

Although not illustrated, it should be appreciated that a similar effect to that described above in connection with Figs. 5 and 6 may be achieved using an electrode wire having a non-uniform cross-sectional area. For example, an electrode comprising:
30 (1) a first group of spirals at the center that are formed using wire having a relatively large cross-sectional width, and (2) second groups of spirals at the ends that are formed using wire having a relatively smaller cross-sectional width, may achieve a similar result. Alternatively, the cross-sectional width of the wire may also increase gradually from the ends to the middle of the coiled electrode. In either such embodiment, the

spacing of the spirals may be uniform or may form some non-uniform pattern like those discussed above in connection with Figs. 5 and 6 (e.g., with larger spaces near the ends of the electrode than in the middle).

Further, although a temperature sensing capability was not described above in connection with the embodiments of Figs. 2-6, it should be appreciated that such a capability may be important during ablation because, without it, overheated tissue may explode or char, releasing debris into the bloodstream. Fig. 7 illustrates a cross-sectional view of the distal end 19 of the catheter 1 in which a temperature sensor 63 is shown disposed within a recess 64 below a conductor 72 of an electrode. The temperature sensor 63 may be a thermocouple, thermistor, or any other device for sensing temperature. Although the temperature sensor 63 is shown disposed below the electrode 61, the sensor 63 may alternatively be disposed above or adjacent the electrode 61, and may be either in direct or indirect contact with the tissue.

The temperature detected at the distal end 19 may be used to provide feedback for control of the ablation energy generator 7 (Fig. 1). As shown, the temperature sensor 63 may be electrically connected to the controller 9 (Fig. 1) via a wire 65, which transmits temperature information along catheter 1 and the cable 11, which connects the catheter 1 to the controller 9. The electrode 61 may be electrically connected to the controller 9 via a wire 67, which transmits RF energy along catheter 1 and the cable 11. The wire 67 may be connected to the end of the electrode (as shown), or may alternatively be connected to a middle portion, or some other portion, of the electrode.

It should be appreciated that any of the embodiments described herein may include a temperature sensor configured and arranged in a similar manner as the temperature sensor 63 of Fig. 7. Alternatively, some embodiments of the invention may employ other suitable temperature control techniques such as impedance control or power titration of the energy applied to the electrode. Further, the duty cycle of applied energy may be selected to allow cooling of the tissue between energy pulses, or the pulse width of the applied energy may be selected to avoid overheating of the tissue.

Figs. 8 and 9 illustrate the distal end 19 of the catheter 1 having non-coiled electrodes in accordance with further embodiments of the invention.

For example, Fig. 8 illustrates an electrode 71 having alternate ridges 73 and grooves 75. The presence of ridges 73 and grooves 75 creates edge effects along the longitudinal length of the electrode 71, at the junctions between the ridges and grooves.

Hence, the edge effects that would normally be present at the ends of a ring-shaped electrode are present in the electrode 71. However, the effects are balanced by the edge effects present towards the center of the electrode 71, which tend to cause a more even distribution of the electric field when the electrode 71 is energized. Although the
5 grooves 75 of the electrode 71 form a spiral, it should be appreciated that a number of alternative groove configurations may be suitable to create the desired effect. For example, circular or linear recesses may be used. Further, although grooves or recesses have been described, holes traversing the thickness of the electrode 71 may instead be formed. The holes, grooves, and recesses described may be formed using a number of
10 techniques including, but not limited to, machining or drilling.

Fig. 9 illustrates an electrode 77 having alternate conductive portions 79 and insulative portions 81 at its surface. The insulative portions 81 may, for example, comprise a dielectric interleaved between the conductive portions 79 in a spiral formation. Alternatively, the insulative portions 81 may be comprise a dielectric layer
15 formed on the surface of the electrode 77. As similarly described above in connection with Fig. 8, the presence of conductive portions 79 and insulative portions 81 creates edge effects along the longitudinal length of the electrode 77, at the junctions between the insulative and conductive portions. With such a configuration, the edge effects at the ends 82 of the electrode 77 are balanced by the edge effects introduced towards the
20 center 84 of the electrode 77, thereby causing a more even distribution of the electric field when the electrode 77 is energized. Although the insulative portions 81 form a spiral in the example shown, it should be appreciated that a number of alternative configurations may be suitable to create the desired effect. For example, circular or linear insulative portions 81 may be used. The insulative portions 81 described may be
25 formed using a number of techniques including, but not limited to, masking or laser stripping of insulation.

It should be appreciated that the technique of using some sort of insulative or dielectric material 81 to form the pattern shown in Fig. 9 may similarly be employed to emulate any of the other electrode patterns described herein, and thereby achieve similar
30 results. For example, rather than winding conductors about the catheter 19 in the manner shown in Figs. 3, 5 and 6 above, a dielectric material could instead be drawn or otherwise disposed onto the portions of a conventional ring electrode at the locations corresponding to the gaps between the spirals illustrated in those examples.

Fig. 10 illustrates the distal end 19 having a pair of electrodes 69a and 69b, which may be configured to create a uniform lesion during ablation. It should be appreciated that two or more electrodes may be included on the distal end 19 for any of the embodiments described herein, and that any combination of described electrodes may be used. Further, any of the electrodes described herein may be movable (e.g., slidable) along the longitudinal length of the catheter, which may assist in the creation of a linear lesion.


In one example, the electrodes 69a and 69b are formed of a material that is an ideal conductor. One exemplary material that is both an ideal conductor and biocompatible is platinum. In accordance with an alternate embodiment of the invention, the electrodes 69a and 69b may be formed of a material that is a non-ideal conductor. A non-ideal conductor may include any material that possesses an electric field gradient within the material when the material is energized. Stainless steel and tungsten are two examples of a material that is both biocompatible and a non-ideal conductor. Non-ideal conductors tend to exhibit more uniform electric field characteristics than ideal conductors. Thus, more even lesion formation may be achieved using a non-ideal conductor. In accordance with a further alternate embodiment of the invention, the electrodes 69a and 69b may be formed of a material that is a semiconductor or metalloid. In one example, a conductive material may be doped to achieve desirable properties. Any of the electrodes described herein may be formed of either an ideal conductor, non-ideal conductor, or semiconductor or metalloid material, in accordance with the invention. The particular material selected may be chosen according to the desired application.

Fig. 11 illustrates the distal end 19 having an arcuate curve 83 and an electrode 85 disposed on a portion of the catheter including the arcuate curve 83. The electrode 85 may be configured to create a uniform lesion during ablation. The arcuate curve 83 may be fixed or may be actively controlled via a steering mechanism of the catheter. It should be appreciated that a portion of the distal end 19 may be curved, bent, or steerable in any of the embodiments described herein in accordance with the invention.

It should be appreciated that the above-described embodiments are merely intended to illustrate possible implementations of the present invention, and various modifications and improvements will readily occur to those skilled in the art. Such modifications and improvements are intended to be within the spirit and scope of the

invention. Accordingly, the foregoing description is by way of example only, and is not intended as limiting.

What is claimed is:



CLAIMS

1. An apparatus for ablating tissue, comprising:
a shaft; and
a tissue-ablating electrode mounted on the shaft, the electrode comprising a first
5 end portion and a middle portion, wherein the first end portion is configured differently
than the middle portion such that, when the electrode is energized, the ratio of a first
density ablation energy that is emitted in a vicinity of the first end portion to a second
density of ablation energy that is emitted in a vicinity of the middle portion is lower than
the ratio would be if the first end portion were configured the same as the middle portion.
10
2. The apparatus of claim 1, wherein the first end portion of the electrode
comprises a first section of a coiled conductor, which first section has spirals that are
spaced apart from one another.
- 15 3. The apparatus of claim 2, wherein the middle portion of the electrode
comprises a second section of the coiled conductor, which second section has spirals that
are closer together than the spirals of the first section of the coiled conductor.
4. The apparatus of claim 3, wherein at least two of the spirals in the second
20 section of the coiled conductor touch each other.
5. The apparatus of any of claims 1-4, wherein the electrode comprises a
coiled conductor having spaces between at least some of its spirals, and a cross-sectional
width of the conductor forming the spirals is narrower in the first end portion than in the
25 middle portion.
6. The apparatus of any of claims 1-5, wherein the electrode comprises at
least two separate coiled conductors having interleaved spirals.
- 30 7. The apparatus of any of claims 1-6, wherein the electrode comprises a
coiled conductor having spaces between adjacent spirals that gradually decrease in size
beginning at each end of the electrode and ending in a middle of the electrode.

8. The apparatus of claim 1, wherein the electrode comprises a conductor of a generally cylindrical shape that is partially masked with a non-conductive substance at least in the first end portion of the electrode.

5 9. The apparatus of claim 1 or 8, wherein the electrode comprises a conductor of a generally cylindrical shape that has a lower density of energy-emitting surface area in the vicinity of the first end portion than in the vicinity of the middle portion.

10 10. The apparatus of any of claims 1-9, in combination with an ablation energy generator to energize the electrode with sufficient energy to ablate tissue.

11. The apparatus of any of claims 1-10, wherein the shaft comprises a distal end of an elongated catheter.

15

12. The apparatus of claim 11, wherein the distal end of the elongated catheter is steerable.

13. The apparatus of any of claims 1-12, wherein the electrode is mounted on
20 the shaft such that at least a portion of an end of the electrode is disposed at least partially below an annular surface of the shaft that is adjacent the end of the electrode.

14. The apparatus of claim 13, wherein the electrode is mounted on the shaft
25 such that at an upper surface of the end of the electrode is substantially flush with the annular surface of the shaft that is adjacent the end of the electrode.

15. The apparatus of any of claims 1-14, wherein the electrode further
comprises a second end portion opposite the first end portion, and wherein the second
end portion is also configured differently than the middle portion such that, when the
30 electrode is energized, the ratio of a third density of ablation energy that is emitted in a
vicinity of the second end portion to the second density of ablation energy that is emitted
in the vicinity of the middle portion is lower than the ratio would be if the second end
portion were configured the same as the middle portion.

16. A apparatus for ablating tissue, comprising:

a shaft; and

5 a tissue-ablating electrode mounted to the shaft, the electrode comprising at least a first end portion and a middle portion, and having at least one energy emitting area configured in a shape other than a coil, wherein at least the middle portion is configured and arranged to introduce edge effects in the middle portion such that, when the conductor is energized, the ratio of a first density of ablation energy emitted in a vicinity of the first end portion to a second density of ablation energy emitted in a vicinity of the
10 middle portion is lower than the ratio would be if the electrode were not configured and arranged to introduce such edge effects in the middle portion.

17. The apparatus of claim 16, wherein the electrode comprises a conductor of a generally cylindrical shape that is partially masked with a non-conductive substance
15 at least in the middle portion so as to introduce edge effects in the middle portion.

18. The apparatus of claim 16 or 17, wherein the electrode comprises a conductor of a generally cylindrical shape that has a lower density of energy-emitting surface area in the vicinity of the first end portion than in the vicinity of the middle
20 portion.

19. The apparatus of any of claims 16-18, in combination with an ablation energy generator operatively coupled to the electrode to enable the ablation energy generator to transmit sufficient energy to the electrode to ablate tissue.
25

20. The apparatus of any of claims 16-19, wherein the shaft comprises a distal end of an elongated catheter.

21. The apparatus of claim 20, wherein the distal end of the elongated
30 catheter is steerable.

22. The apparatus of any of claims 16-21, wherein the electrode is mounted on the shaft such that at least a portion of an end of the electrode is disposed at least partially below an annular surface of the shaft that is adjacent the end of the electrode.

5 23. The apparatus of claim 22, wherein the electrode is mounted on the shaft such that at an upper surface of the end of the electrode is substantially flush with the annular surface of the shaft that is adjacent the end of the electrode.

10 24. The apparatus of any of claims 16-23, wherein the electrode further comprises a second end portion opposite the first end portion, and wherein at least the middle portion is configured and arranged to introduce edge effects in the middle portion such that, when the conductor is energized, the ratio of a third density of ablation energy emitted in a vicinity of the second end portion to the second density of ablation energy emitted in the vicinity of the middle portion is lower than the ratio would be if the
15 electrode were not configured and arranged to introduce such edge effects in the middle portion.

 25. A apparatus for ablating tissue, comprising:
 a shaft; and
20 a tissue-ablating electrode mounted on the shaft, the electrode comprising at least two separate coiled conductors having interleaved spirals.

 26. The apparatus of claim 25, wherein the electrode comprises at least three separate coiled conductors having interleaved spirals.

25 27. The apparatus of claim 25 or 26, in combination with an ablation energy generator operatively coupled to the at least two conductors to enable the ablation energy generator to transmit sufficient energy to the at least two conductors to ablate tissue.

30 28. The combination of claim 27, in further combination with a controller to control transmission of ablation energy from the ablation energy generator to the at least two conductors in a pulsed, sequential fashion.

29. The apparatus of any of claims 25-28, wherein the shaft comprises a distal end of an elongated catheter.

30. The apparatus of claim 29, wherein the distal end of the elongated
5 catheter is steerable.


31. The apparatus of any of claims 25-30, wherein the electrode is mounted on the shaft such that at least a portion of an end of the electrode is disposed at least partially below an annular surface of the shaft that is adjacent the end of the electrode.
10

32. The apparatus of claim 31, wherein the electrode is mounted on the shaft such that at an upper surface of the end of the electrode is substantially flush with the annular surface of the shaft that is adjacent the end of the electrode.

33. An apparatus for ablating tissue, comprising:
a shaft; and
a tissue-ablating electrode comprising a coiled conductor having spaces between at least some of its adjacent spirals, the electrode being mounted on the shaft such that at least a portion of an end of the electrode is disposed at least partially below an annular
15 20 surface of the shaft that is adjacent the end of the electrode.





34. The apparatus of claim 33, wherein the electrode is mounted on the shaft such that at an upper surface of the end of the electrode is substantially flush with the annular surface of the shaft that is adjacent the end of the electrode.
25

35. A apparatus for ablating tissue, comprising:
a shaft; and
a tissue-ablating electrode mounted to the shaft, the electrode comprising an end portion and a middle portion, and having at least one energy-emitting area configured in
30 a shape other than a coil, the electrode further comprising means for introducing edge effects in at least the middle portion.



JC20 Rec'd PCT/PTO 1 6 MAY 2005

THIS PAGE BLANK (USP:U)

**FIG. 2****FIG. 3****FIG. 4****FIG. 5**

JC20 Rec'd PCT/PTO 1 6 MAY 2005

THIS PAGE BLANK (USP 0)




FIG. 6




FIG. 7




FIG. 8






FIG. 9

JC20 Rec'd PCT/PTO 1 6 MAY 2005

THIS PAGE BLANK (USPTO)

4/4

**FIG. 10****FIG. 11**

JC20 Rec'd PCT/PTO 1 6 MAY 2005

THIS PAGE BLANK (USPTO)

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 03/36488

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A61B18/14

16 MAY 2005

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 1 151 726 A (BIOSENSE WEBSTER INC) 7 November 2001 (2001-11-07) paragraph '0019!	1,8-17, 19-24,35 2
X	US 6 287 306 B1 (PENDAKANTI RAJESH ET AL) 11 September 2001 (2001-09-11) column 4, line 37 - line 64; figure 4	1,10-12, 15,16, 19-21,35
X	US 2002/072744 A1 (BOWMAN BRETT ET AL) 13 June 2002 (2002-06-13) paragraph '0045!; figure 8	25-27, 29-32
X	US 6 280 441 B1 (RYAN THOMAS PATRICK) 28 August 2001 (2001-08-28) column 6, line 32 - line 50; figure 6 -/--	25-27, 29-32

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

G document member of the same patent family

Date of the actual completion of the international search

16 April 2004

Date of mailing of the international search report

22/04/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Mayer-Martenson, E

INTERNATIONAL SEARCH REPORT

Application No

/US 03/36488

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 6 456 863 B1 (FLEISCHMAN SIDNEY D ET AL) 24 September 2002 (2002-09-24) column 4, line 65 -column 5, line 29; figures 3,4 ---	33,34
Y	US 6 030 382 A (FLEISCHMAN SIDNEY D ET AL) 29 February 2000 (2000-02-29) column 13; claim 1 ---	2,33,34
A		1
A	US 6 413 255 B1 (STERN ROGER A) 2 July 2002 (2002-07-02) column 6, line 40 - line 46; figure 3 -----	1

INTERNATIONAL SEARCH REPORT

International Application No. PCT/ US 03 /36488

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims: 1-32,35

electrodes with different mid and end portions

2. Claims: 33,34

electrodes with end portion partly covered by shaft

INTERNATIONAL SEARCH REPORT

national application No.
PCT/US 03/36488

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☒ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 03/36488

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 1151726	A	07-11-2001	US 6475214 B1 EP 1151726 A1 JP 2002119519 A	05-11-2002 07-11-2001 23-04-2002
US 6287306	B1	11-09-2001	US 2004039382 A1	26-02-2004
US 2002072744	A1	13-06-2002	US 6346102 B1 US 6068626 A US 5954715 A AU 758284 B2 AU 7148198 A CA 2311375 A1 EP 1005296 A1 WO 9855046 A1	12-02-2002 30-05-2000 21-09-1999 20-03-2003 21-12-1998 10-12-1998 07-06-2000 10-12-1998
US 6280441	B1	28-08-2001	NONE	
US 6456863	B1	24-09-2002	US 6078830 A	20-06-2000
US 6030382	A	29-02-2000	US 5797905 A US 6245068 B1 US 2001014770 A1 CA 2237563 A1 DE 69621845 D1 DE 69621845 T2 EP 0955917 A1 ES 2176512 T3 JP 2000500363 T WO 9717904 A1 CA 2174129 A1 EP 0754075 A1 JP 9509069 T WO 9510318 A1 US 6197021 B1 US 2002193790 A1 US 2003065322 A1 US 6357447 B1 US 6471699 B1 US 6500172 B1 US 6106522 A US 5810802 A US 6129724 A US 5991650 A	25-08-1998 12-06-2001 16-08-2001 22-05-1997 18-07-2002 02-01-2003 17-11-1999 01-12-2002 18-01-2000 22-05-1997 20-04-1995 22-01-1997 16-09-1997 20-04-1995 06-03-2001 19-12-2002 03-04-2003 19-03-2002 29-10-2002 31-12-2002 22-08-2000 22-09-1998 10-10-2000 23-11-1999
US 6413255	B1	02-07-2002	US 2002151887 A1 US 2002156471 A1 US 2003216728 A1 US 2004034346 A1 US 2003199866 A1 US 2004002704 A1 US 2004000316 A1 US 2003212393 A1 US 2004030332 A1 US 2004002705 A1 US 2003220635 A1 AU 3741500 A CA 2364098 A1 EP 1158919 A1	17-10-2002 24-10-2002 20-11-2003 19-02-2004 23-10-2003 01-01-2004 01-01-2004 13-11-2003 12-02-2004 01-01-2004 27-11-2003 28-09-2000 14-09-2000 05-12-2001

INTERNATIONAL SEARCH REPORT

Initial Application No

US 03/36488

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 6413255	B1	JP 2002537939 A WO 0053113 A1	12-11-2002 14-09-2000
<hr/>			